



## DMX CONFETTI BLOWER



### FEATURES:

- Small Footprint (10" x 10")
- Up to 50FT Confetti Height
- Clog Free Output
- Quick Connect CO2 Input
- Digital DMX Interface
- 0-90° Output Angle (Adjustable)
- Truss Mountable (Integrated 1/2" Nut in Yoke)
- Pull handle for easy Positioning & Portability
- Integrated Silencer for Quieter Operation

### DMX SPECS:

- Manufactured by Doug Fleenor Design
- 1 Channel DMX Operation (CH 1 > 128)
- Power Control Mode (CH 000)
- Available with 3 or 5 Pin DMX In & Out

### APPLICATIONS:

For use with Paper or Mylar Confetti. Typical Applications Include:

- Nightclubs
- Music Festivals
- Theme Parks
- Sporting Events
- Graduations
- Weddings

### CONSTRUCTION:

- 18GA Steel Body Components
- Textured Black Powder Coating
- Ventilation Perforations in Body
- Built & Assembled in USA

### CONSUMPTION:

- CO2 - Approx 1LB per Second (Works with Siphon or Standard CO2 Tanks)
- Tissue - Approx 1/3LB per Second
- Mylar - Approx 2/3LB per Second

### FILL CAPACITY:

- Tissue - Approx 3-4LB
- Mylar - Approx 4-6LB

### ELECTRICAL:

- 110-120V or 220-240V AC
- 25W Consumption
- Neutrik True1 Input



## DMX CONFETTI BLOWER

